

Operating system	Embedded Linux
Processor	HI3518E(1.0, 1.3 MP) HI3518C(2.0MP)
Image sensor	1.0MP:1/4" 1.0 megapixel progressive CMOS sensor 1.3MP:1/3" 1.3 megapixel progressive CMOS sensor 2.0MP:1/3" 2.0 megapixel progressive CMOS sensor
IR-CUT	Support
Lens	C/CS 4mm 3 Megapixel Fixed Lens
Minimum illumination	0.01Lux
Compression standard	
Audio compression	G.726/G.711 (Default is G.711)
Compressed transport stream	32Kbps-6Mbps, can self-defined, default is 2536Kbps
Function	
Storage	Max 128G Micro SD Card
Motion detection	can set 4 independent detection area (sensitivity is 1-100 adjustable)
Alarm linkage	sending pictures to named mailbox; upload pictures and video to FTP server; pictures and videos to SD Card
4G Function	Support FDD-LTE, TDD-LTE, WCDMA/HSPA+, TD-SCDMA, GSM/GPRS/EDGE
Common specification	
Package	4G WIFI Camera Solar Panel
Total Weight	14.5KG
Package Size	72×23.5×76cm
Working temperature	-20℃~+55℃
Working Humidity	10%~95%RH
Power supply	DC12V 2A

Protection range	IP66
power consumption:	3W(IR LED: Off); 15W(IR LED: ON)